

 tecno.mec	Codice raccordo <i>Coupling code</i> 200033
Via Canale 114 – 42013 CASALGRANDE (RE) – ITALY info@tecnomec.com	

SCHEDA TECNICA - PRODUCT DATASHEET		
ITEM TYPE: QUICK COUPLING	No: 200033-10-25	Date: 09.10.2025

Raccordo rapido ad innesto a sfere ARS-TM 250 BAR G 3/8" F – G 3/8" F
<i>Ball quick coupling</i> ARS-TM 250 BAR G 3/8" F – G 3/8" F

PRESSIONE NOMINALE <i>RATED PRESSURE</i>	250 BAR - 25 MPa (3625 PSI)
PRESSIONE CONSENTITA <i>PERMISSIBLE PRESSURE</i>	290 BAR - 29 MPa (4200 PSI)
PORTATA MASSIMA <i>MAX. FLOW RATE</i>	50 l/min - 13.2 USG p.m
TEMPERATURA MASSIMA <i>MAX: WORKING TEMPERATURE</i>	100° C - (212° F)
(A) PERNO IN ACCIAIO TEMPRATO/ZINCATO E (B) CORPO IN OTTONE CON GUARNIZIONI OR IN NBR <i>(A) PIN IN HARDENED GALVANIZED STEEL AND (B) BODY IN BRASS WITH NBR O RINGS .</i>	

Misure di ingombro - Overall dimensions

